



SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/7

Basics of Bling Tyre and Trim

Revision 0

Revision date 2015-07-24

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Basics of Bling Tyre and Trim
--------------	-------------------------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU21] Consumer uses: Private households (= general public = consumers); [PC15] Non-metal-surface treatment products; [AC1] Vehicles; ----- [SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [PC15] Non-metal-surface treatment products; [AC1] Vehicles;
-------------	---

1.3. Details of the supplier of the safety data sheet

Company	Dodo Juice Limited
Address	Unit 10 Golds Nurseries Business Park Jenkins Drive Elsenham Bishops Stortford CM22 6JX UK
Web	www.dodojuice.com
Telephone	+44(0)1279 813222
Email address of the competent person	factory@dodojuice.com

1.4. Emergency telephone number

Emergency telephone number	+44(0)7891 096802
Company	Dodo Juice Ltd 24 hr

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	Xn; R65 R66 Symbols: Xn: Harmful.
Main hazards	Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.
2.1.2. Classification - EC 1272/2008	Asp. Tox. 1: H304;

2.2. Label elements

Hazard pictograms	
-------------------	---

Basics of Bling Tyre and Trim

Revision 0

Revision date 2015-07-24

2.2. Label elements

Signal Word	Danger
Hazard Statement	Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Precautionary Statement: Response	P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/ . P331 - Do NOT induce vomiting.
Precautionary Statement: Storage	P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to hazardous waste.

2.3. Other hazards

Other hazards	May cause irritation to eyes and respiratory system.
---------------	--

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics			920-901-0		60 - 70%	Xn; R65 R66	
(R)-p-Mentha-1,8-diene (D-Limonene)	601-029-00-7	5989-27-5	227-813-5			R10 Xi; R38 R43 N; R50/53	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics			920-901-0		60 - 70%	EUH066; Asp. Tox. 1: H304;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing stops, provide artificial respiration.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse.
Ingestion	If swallowed, seek medical advice immediately and show this container or label. DO NOT INDUCE VOMITING.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	None.
Eye contact	None.
Skin contact	None.
Ingestion	None.

4.3. Indication of any immediate medical attention and special treatment needed

Ingestion	Aspiration hazard. May be fatal if swallowed and enters airways.
-----------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam. Do NOT use water jet.
--	---

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

Basics of Bling Tyre and Trim

Revision 0

Revision date 2015-07-24

5.3. Advice for firefighters

Self-contained breathing apparatus. Wear protective clothing.

Further information

Combustible liquid.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear suitable protective equipment.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

6.4. Reference to other sections

See section 6.1 for further information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ensure adequate ventilation of the working area. Avoid contact with skin. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

7.3. Specific end use(s)

See section 1 for further information.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

(R)-p-Mentha-1,8-diene (D-Limonene)	WEL 8-hr limit ppm: 100	WEL 8-hr limit mg/m3:
	WEL 15 min limit ppm: 150	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Basics of Bling Tyre and Trim (Red Mist Tropical)	WEL 8-hr limit ppm: 171	WEL 8-hr limit mg/m3: 1200
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	WEL 8-hr limit ppm: 171	WEL 8-hr limit mg/m3: 1200
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

8.2. Exposure controls

Basics of Bling Tyre and Trim

Revision 0

Revision date 2015-07-24

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Self-contained breathing apparatus. Wear protective clothing.
8.2.3. Environmental exposure controls	See section 6, 7, 12, 13 for further information.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Yellow
Odour	Perfumes
Initial boiling point	170 - 250 °C
Flash point	61 °C
Evaporation rate	0.05 n-butyl acetate = 1
Upper Explosive Limit	7 %
Lower Explosive Limit	0.6 %
Vapour pressure	40 Pa
Relative density	0.817 (H ₂ O = 1 @ 20 °C)
Autoignition temperature	200 °C
Viscosity	7 sec. 3 mm (ISO 2431)
Solubility	Insoluble in water

9.2. Other information

VOC (Volatile organic compounds)	572 g/l
----------------------------------	---------

SECTION 10: Stability and reactivity

10.1. Reactivity

	Stable under normal conditions.
--	---------------------------------

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	No Significant Hazard.
--	------------------------

10.4. Conditions to avoid

	Avoid sparks, flames, heat and sources of ignition.
--	---

10.5. Incompatible materials

	Strong oxidising agents.
--	--------------------------

10.6. Hazardous decomposition products

	Will not decompose if stored and used as recommended.
--	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	No Significant Hazard.
----------------	------------------------

Basics of Bling Tyre and Trim

Revision 0

Revision date 2015-07-24

11.1. Information on toxicological effects

Skin corrosion/irritation	May cause irritation to skin.
Serious eye damage/irritation	May cause irritation to eyes.
Respiratory or skin sensitisation	No sensitization effects reported.
Germ cell mutagenicity	No mutagenic effects reported.
Carcinogenicity	No carcinogenic effects reported.
Reproductive toxicity	No teratogenic effects reported.
STOT-single exposure	No Significant Hazard.
STOT-repeated exposure	No Significant Hazard.
Aspiration hazard	May be fatal if swallowed and enters airways.

11.1.4. Toxicological Information

(R)-p-Mentha-1,8-diene	Oral Rat LD50: 4400mg/kg	Dermal Rabbit LD50: >5000mg/kg
Basics of Bling Tyre and Trim	Inhalation Rat LC50/8 h: 5000mg/m ³ Dermal Rabbit LD50: 5000mg/kg	Oral Rat LD50: 5000mg/kg
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Inhalation Rat LC50/8 h: >5000mg/kg Dermal Rabbit LD50: >5000mg/kg	Oral Rat LD50: >5000mg/kg

SECTION 12: Ecological information

12.1. Toxicity

(R)-p-Mentha-1,8-diene	Daphnia EC50/48h: 69.6 mg/l	Fathead minnows LC50/96h: 0.702mg/l
Basics of Bling Tyre and Trim	Daphnia EC50/48h: 1000 mg/l Fish LC50/96h: 1000 mg/l	Algae IC50/72h: 1000 mg/l
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Daphnia EC50/48h: 1000 mg/l Fish LC50/96h: 1000 mg/l	Algae IC50/72h: 1000 mg/l

12.2. Persistence and degradability

	Evaporates readily.
--	---------------------

12.3. Bioaccumulative potential

	No data is available on this product.
--	---------------------------------------

Partition coefficient

	Hydrocarbons, C11-C13, isoalkanes, <2% aromatics No data available
--	---

12.4. Mobility in soil

	No data available.
--	--------------------

12.5. Results of PBT and vPvB assessment

	PBT no. vPvB no.
--	------------------

12.6. Other adverse effects

	No known adverse environmental effects.
--	---

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

Disposal methods

Basics of Bling Tyre and Trim

Revision 0

Revision date 2015-07-24

Disposal methods	
	Contact a licensed waste disposal company.
Disposal of packaging	
	Empty containers can be sent for disposal or recycling.
SECTION 14: Transport information	
14.1. UN number	
	The product is not classified as dangerous for carriage.
14.2. UN proper shipping name	
	The product is not classified as dangerous for carriage.
14.3. Transport hazard class(es)	
	The product is not classified as dangerous for carriage.
14.4. Packing group	
	The product is not classified as dangerous for carriage.
14.5. Environmental hazards	
	The product is not classified as dangerous for carriage.
14.6. Special precautions for user	
	The product is not classified as dangerous for carriage.
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	
	The product is not classified as dangerous for carriage.
SECTION 15: Regulatory information	
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture	
Regulations	REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
15.2. Chemical safety assessment	
	No data available.
SECTION 16: Other information	
Other information	
Text of risk phrases in Section 3	R10 - Flammable R38 - Irritating to skin. R43 - May cause sensitisation by skin contact. R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 - Harmful: may cause lung damage if swallowed. R66 - Repeated exposure may cause skin dryness or cracking.
Text of Hazard Statements in Section 3	EUH066 - Repeated exposure may cause skin dryness or cracking. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Maximum content of VOC	572 g/l.
Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information

Basics of Bling Tyre and Trim

Revision 0

Revision date 2015-07-24

Further information

	relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	---
